

imagine[®]

your home reinvented.



WINDCODE[®]

ARE YOU READY FOR THE STORM?
Based on ASCE7-10 code

Clopay[®]

America's Favorite Garage Doors[®]



WINDCODE® GARAGE DOORS

DETERMINE YOUR WINDCODE® RATING

Clopay assigns a WINDCODE® "W" rating to our doors based on code requirements determined by wind speed in miles per hour (MPH), home exposure and home structural type.

STEP 1:

- Determine the minimum wind speed (MPH) your door must meet or exceed from the map below, or go to www.atcouncil.org/windspeed.


This map is to help determine your "W" rating, and should be used as a guideline only. Contact your local building code official to determine the proper wind load requirements in your area.

If you live in Florida, please refer to the Florida WindCode® Edition.

Please refer to Risk Category II when using ATC Wind Speed calculator for residential applications.

This ASCE7-10 map is used with permission from ASCE.

For other building codes and standards, please visit the WindCode calculator below.



STEP 2:


- Determine if your home is in an Exposure B or Exposure C region.

Exposure B typically urban or suburban setting or wooded terrain.

Exposure C open terrain with scattered obstructions, flat open ground, grasslands or shorelines in hurricane-prone regions.

STEP 3:

- Determine the structural type of your home.



- Using wind speed (MPH), exposure and structural type, find your WINDCODE® "W" rating in the charts on page 3.

Due to the complexity of installing WINDCODE® garage doors, meeting codes and pulling permits, we highly recommend professional installation.

STEP 4:

- Using wind speed (MPH), exposure and structural type, find your required design pressure and WINDCODE® "W" rating in the charts below.

Note: It is important to also contact your homeowner's insurance company. Many insurance companies may require or encourage doors that are different than required by building code.

Additional requirements may be requested by building code officials such as flood resistant construction.

Typically, garage doors are **NOT** part of this requirement. See details in DASMA TDS-184.

HELPFUL LINKS:

For Texas wind storm program information visit:

www.tdi.texas.gov/wind/index.html

For Industry Technical Data Sheet (DASMA TDS) visit:

www.dasma.com/dasma-pages/DASMA-technical-data-sheets.asp

For easy access to up to date drawings and evaluation reports, visit: www.clopaydoor.com/residential/windcode-residential-information/residential-windcode-calculator

DESIGN PRESSURES

The design wind load pressure rating of a door is expressed in PSF (pounds per square foot). The design pressure of the door must equal or exceed the design pressure for the garage door opening in which a door is to be installed. Design pressure has positive and negative values.

GARAGE DOOR WIND LOAD GUIDE – VALUES IN PSF												
Mean Roof Height	Door Size	Based on ASCE7-10, Exposure B, 115 – 200 MPH Ultimate Design Wind Speed, MPH (V _{ult})										
Ultimate Wind Speed →		115 MPH	120 MPH	130 MPH	140 MPH	150 MPH	160 MPH	170 MPH	180 MPH	190 MPH	200 MPH	
Less Than 30 Feet	Single 9' × 7'	12.5 –14.2	13.7 –15.5	16.1 –18.2	18.5 –20.9	21.3 –24.1	24.3 –27.5	27.6 –31.2	30.6 –34.6	34.2 –38.6	38.0 –43.0	
	Double 16' × 7'	12.0 –13.4	13.1 –14.6	15.5 –17.2	17.7 –19.7	20.4 –22.7	23.3 –26.0	26.4 –29.4	29.3 –32.6	32.7 –36.5	36.4 –40.6	
Equivalent Nominal Wind Speed →		89 MPH	93 MPH	101 MPH	108 MPH	116 MPH	124 MPH	132 MPH	139 MPH	147 MPH	155 MPH	
Mean Roof Height	Door Size	Based on ASCE7-10, Exposure C, 115 – 200 MPH Ultimate Design Wind Speed, MPH (V _{ult})										
Ultimate Wind Speed →		115 MPH	120 MPH	130 MPH	140 MPH	150 MPH	160 MPH	170 MPH	175 MPH	180 MPH	190 MPH	200 MPH
15 Feet Single Story	Single 9' × 7'	15.2 –17.2	16.6 –18.8	19.6 –22.2	22.4 –25.3	25.9 –29.2	29.5 –33.4	33.5 –37.8	35.3 –39.9	37.1 –42.0	41.5 –46.9	46.2 –52.2
	Double 16' × 7'	14.6 –16.2	15.9 –17.7	18.8 –20.9	21.5 –23.9	24.8 –27.6	28.3 –31.5	32.1 –35.7	33.8 –37.7	35.5 –39.6	39.8 –44.3	44.2 –49.3
25 Feet Double Story	Single 9' × 7'	16.8 –19.0	18.4 –20.8	21.7 –24.5	24.8 –28.0	28.6 –32.3	32.7 –36.9	37.0 –41.8	39.0 –44.1	41.1 –46.4	45.9 –51.9	51.1 –57.7
	Double 16' × 7'	16.1 –18.0	17.6 –19.6	20.8 –23.1	23.7 –26.5	27.4 –30.5	31.3 –34.9	35.5 –39.5	37.4 –41.7	39.3 –43.8	44.0 –49.0	48.9 –54.5
Equivalent Nominal Wind Speed →		89 MPH	93 MPH	101 MPH	108 MPH	116 MPH	124 MPH	132 MPH	136 MPH	139 MPH	147 MPH	155 MPH

The design pressures listed are the minimum required. Recommended WINDCODE® levels typically meet or exceed the required design pressures.

MPH = miles per hour PSF = pounds per square foot

WINDCODE® “W” RATING GUIDE											
EXPOSURE B											
Structural Type	115 MPH	120 MPH	130 MPH	140 MPH	150 MPH	160 MPH	170 MPH	180 MPH	190 MPH	200 MPH	
One Story	W1	W2	W3	W3	W4	W5	W5	W6	W6	W7	
Two Story	W1	W2	W3	W3	W4	W5	W5	W6	W6	W7	
EXPOSURE C											
Structural Type	115 MPH	120 MPH	130 MPH	140 MPH	150 MPH	160 MPH	170 MPH	175 MPH	180 MPH	190 MPH	200 MPH
One Story	W2	W3	W3	W4	W5	W5/W6	W6/W7	W6/W7	W7	W7	W8
Two Story	W3	W3	W4	W5	W5/W6	W6	W6/W7	W7/W8	W7/W8	W8	W9

MPH = miles per hour



Coachman® Design 21 with SQ24 Window Design



WINDCODE® GARAGE DOORS

**STORM READY® – NO POSTS, PINS OR EXTRA SETUP.
JUST CLOSE AND LOCK YOUR DOOR.**


WINDCODE® BENEFITS

- No attachments to the floor or structure required
- No extra posts, pins, parts or setup necessary
- Storm ready, simply close and lock your door

STANDARD GARAGE DOOR



WINDCODE® GARAGE DOORS



- A** Patented T-Strut design strengthens door
- Heavy-duty commercial grade track provides additional strength and durability
- B**
- Commercial-duty steel rollers and hardware withstand more severe wind pressures
- C**

CLOPAY'S WINDCODE® GARAGE DOORS

Clopay's WINDCODE® garage doors are designed to help withstand high winds resulting from tropical storms and other strong wind-related weather events. This user-friendly system assists you in selecting the right garage door for your area and building structure.

DESIGN OPTIONS

Clopay's WINDCODE® product offering has the widest range of panel styles, colors and window designs available today. Accent the design of your home while providing the protection you need against strong winds. Choose from various panel designs and Designer or Decorative windows for that extra curb appeal. Impact-resistant windows are available in many different colors and wind load levels.

DESIGNED AND TESTED TO WITHSTAND STRONG WINDS

All Clopay WINDCODE® doors have been designed and tested to meet various code requirements. Additional interior horizontal steel reinforcement along with increased hardware and springing components are installed so your door is ready when a storm hits. No posts or pins are required to secure your door if you are not there. Just lock your door.

OPTIONS AND UPGRADES

HEAVY HARDWARE UPGRADE

- Nylon ball bearing rollers for quiet, long-lasting operation
- Heavy-duty 14 gauge hinges for smooth worry-free operation



intellicore®
insulation technology

**COOLER
QUIETER
STRONGER**

Garage doors featuring Intellicore® insulation technology represent the ultimate smart choice for homeowners. Clopay's Intellicore® insulation is a proprietary polyurethane foam that is injected into a garage door, expanding to fill the entire structure. The result is a door with incredible strength and durability. Its dense insulation also produces a quieter door, while its industry-leading R-values (up to 20.4) provide year-round comfort and improved energy efficiency.



Look for the Intellicore® insulation technology icon throughout this brochure on select door models.

CANYON RIDGE® modern




Canyon Ridge® Modern door designs feature key elements of contemporary architecture: clean, horizontal lines with mid-century appeal, sleek window styles and aluminum accents.

STYLE AND CONSTRUCTION

- Plank design: Faux-wood doors with Intellicore® polyurethane insulation (R-value 20.4).
- Metal Inlay design: Faux-wood doors with Intellicore® polyurethane insulation (R-value 18.4).
- Full-View design: Faux-wood doors with Intellicore® polyurethane insulation (R-value 6.3).
- Replaceable vinyl bottom weatherseal in a rust-resistant aluminum retainer helps seal out the elements.

Calculated door section R-value is in accordance with DASMA TDS-163.

MATERIAL DESIGN OPTIONS



FINISHING AND CARE: Proper care and maintenance are imperative for long-term performance and appearance of Canyon Ridge® garage doors. Periodic inspection and maintenance of the composite cladding and overlays is required. Complete finishing and maintenance instructions are provided with the door and are also available from your Clopay Dealer or online at www.clopaydoor.com.


COLOR OPTIONS



*Black and White Finish available only on Mahogany composite cladding and overlays.
Doors can be ordered primed for those homeowners wishing to custom paint or stain their doors.
Door stain color will vary slightly within a door due to the finishing process. Due to the printing process, colors may vary.

DOOR DESIGNS

Custom designs available, contact Clopay for availability.




WINDOW OPTIONS




Available only on Plank door designs. Both available on single car and double car doors.

PLANK WINDOW CONFIGURATIONS



Note: Configurations are illustrated from outside garage. When ordering, window locations are identified from inside garage looking out. Please keep in mind to avoid windows ordered in incorrect location. Additional configurations available. See your Clopay Dealer for more information.

SPECIALTY GLASS OPTIONS




WINDCODE® AVAILABILITY CHART										
Common Door Widths		W1	W3	W4	W5	W6		W7	W8	
Model CRM	8', 9' Wide Door	S +13/-15 PSF	SELECT W6	SELECT W6	SELECT W6	PLANK/FULL-VIEW FW S +38/-42 PSF	METAL INLAY FT W S +38/-44 PSF	SELECT W8	PLANK/FULL-VIEW FW S +54/-62 PSF	METAL INLAY FW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	PLANK/FULL-VIEW FW S +38/-42 PSF	METAL INLAY FT W S +38/-42 PSF	SELECT W8	PLANK/FULL-VIEW FW S +50/-56 PSF	METAL INLAY FW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	PLANK/FULL-VIEW FW S +38/-42 PSF	METAL INLAY FT W S +38/-42 PSF	SELECT W8	PLANK/FULL-VIEW FW S +46/-52 PSF	METAL INLAY FW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	PLANK/FULL-VIEW F* +38/-42 PSF	METAL INLAY FT W S +38/-42 PSF			
S Standard Windows Available Impact Rated						W Patented Impact Windows Available F Florida Approved		D Dade County Approved T Texas Department of Insurance Approved		

For W6-W8 doors over 10'2" wide, add 2" to the door opening.

*Product approval pending.

CANYON RIDGE® carriage house

5-LAYER CONSTRUCTION



Canyon Ridge® Carriage House 5-Layer doors are constructed of durable, low-maintenance steel and composite. These faux-wood alternatives offer the best of both worlds — the realism and beauty of a natural stained wood appearance combined with the strength and energy efficiency of insulated steel.

STYLE AND CONSTRUCTION

- 5-layer construction, 2" thick Intellcore® polyurethane insulation (R-value 20.4).
- Attractive beveled edge, clip-in grilles are removable for easy cleaning.
- Replaceable vinyl bottom weatherseal in a rust-resistant aluminum retainer helps seal out the elements.
- 10-ball nylon rollers for quiet operation.
- Heavy-duty 14 gauge steel hinges for long-lasting performance.

Calculated door section R-value is in accordance with DASMA TDS-163.

DOOR DESIGNS

Custom designs available, contact Clopay for availability.

SERIES 1



SERIES 2



SERIES 3



Doors shown in Dark Finish with Clear Cypress cladding and Clear Cypress overlay. Design 01 does not have an overlay.

WINDCODE® AVAILABILITY CHART								
Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Model CAN	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	FS +30/-32 PSF	FTDWS +38/-44 PSF	SELECT W8	FDW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL F +37.5/-40 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF TAPERED STRUT FDW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL F +37.5/-40 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF TAPERED STRUT FDW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	C-CHANNEL F +37/-37 PSF TAPERED STRUT FTDWS +38/-42 PSF		
S Standard Windows Available Impact Rated			W Patented Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved		

For W6-W8 doors over 10'2" wide, add 2" to the door opening.

CANYON RIDGE® carriage house

5-LAYER CONSTRUCTION



MATERIAL DESIGN OPTIONS

CLADDING MATERIALS



Clear Cypress



Mahogany



Pecky Cypress

OVERLAY MATERIALS



Clear Cypress



Mahogany

COLOR OPTIONS



Medium Finish




Dark Finish



Walnut Finish



Slate Finish



Black Finish*



White Finish*



Primed
(No Finish)

Cladding and overlay material options may be mixed and matched.

FINISHING AND CARE: Proper care and maintenance are imperative for long-term performance and appearance of Canyon Ridge® garage doors. Periodic inspection and maintenance of the composite cladding and overlays are required. Complete finishing and maintenance instructions are provided with the door and are also available from your Clopay Dealer or online at www.clopaydoor.com.

*Black and White Finish available only on Mahogany cladding and overlays.


Two-tone doors are available. To see all available options go to: dls.clopay.com.

Doors can be ordered primed for those homeowners wishing to custom paint or stain their doors. Door stain color will vary slightly within a door due to the finishing process. Due to the printing process, colors may vary.

WINDOW OPTIONS



REC11




REC13



REC14



SQ23



SQ24



ARCH1



ARCH13



ARCH14



ARCH3




ARCH4


Window grilles are Clear Cypress texture. Windows not available on Designs 01, 31, 32, 33, 34, 35, 36, 37 and 38. Double door designs also available.

Standard windows available on the following widths only: 6'2", 8'0", 9'0", 10'0", 10'2", 12'0", 12'2", 13'6", 15'0", 15'2", 15'6", 15'8", 16'0", 16'2", 18'0", 18'2", 20'0", 20'2".

Impact windows available on the following widths only: 8'0", 9'0", 10'0", 12'2", 16'2", 18'2". To view additional designs, windows and top sections available, please visit www.clopaydoor.com.

 Impact rated windows available.

SPECIALTY GLASS OPTIONS



Clear



Frosted



Seeded



Obscure



Rain



Clear Polycarbonate

Windows are available insulated in clear, frosted, seeded, obscure and rain.

Impact rated windows are available in clear polycarbonate and may have a wavy appearance.

CANYON RIDGE® carriage house

4-LAYER CONSTRUCTION



Canyon Ridge® Carriage House 4-Layer base doors are available in Ultra-Grain® finish and solid colors for the perfect complement to your home. The overlay materials are molded from actual wood to reproduce the natural texture and grain patterns of the species that they emulate. The combination of steel and overlay creates a distinct look.


STYLE AND CONSTRUCTION

- 4-layer construction, 2" thick IntellCore® polyurethane insulation (R-value 18.4).
- Attractive beveled edge, clip-in grilles are removable for easy cleaning.
- Replaceable vinyl bottom weatherseal in a rust-resistant aluminum retainer helps seal out the elements.
- 10-ball nylon rollers for quiet operation.
- Heavy-duty 14 gauge steel hinges for long-lasting performance.

Calculated door section R-value is in accordance with DASMA TDS-163.

DOOR DESIGNS

Custom designs available, contact Clopay for availability.



All doors shown in Medium Finish with Clear Cypress overlay.

WINDCODE® AVAILABILITY CHART								
Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Model CAN	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	FS +30/-32 PSF	FTDWS +38/-44 PSF	SELECT W8	FTDWS +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL F +37.5/-40 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL F +37.5/-40 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	C-CHANNEL F +37/-37 PSF		
S Standard Windows Available Impact Rated			W Patented Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved		

For W6-W8 doors over 10'2" wide, add 2" to the door opening.

CANYON RIDGE® carriage house

4-LAYER CONSTRUCTION



MATERIAL DESIGN OPTIONS

STEEL BASE MATERIAL



Ultra-Grain® Finish Clear Cypress
or Solid Color Steel

Composite cladding is not present on
Carriage House 4-Layer doors.

OVERLAY MATERIALS




Clear Cypress



Mahogany

FINISHING AND CARE: Proper care and maintenance are imperative for long-term performance and appearance of Canyon Ridge® garage doors. Periodic inspection and maintenance of the composite cladding and overlays are required. Complete finishing and maintenance instructions are provided with the door and are also available from your Clopay Dealer or online at www.clopaydoor.com.

COLOR OPTIONS



Ultra-Grain® Cypress
Medium Finish




Ultra-Grain® Cypress
Walnut Finish



Ultra-Grain® Cypress
Slate Finish



Black Finish*



White Finish*



Primed
(No Finish)

*Black and White Finish available only on Mahogany overlays.


Two-tone doors are available. To see all available options go to: dis.clopay.com.

Doors can be ordered primed for those homeowners wishing to custom paint their doors. Note: Primed solid steel base is a brown color. Door stain color will vary slightly within a door due to the finishing process. Due to the printing process, above colors may vary.

WINDOW OPTIONS



REC11




REC13



REC14



SQ23



SQ24



ARCH1



ARCH13



ARCH14



ARCH3



ARCH4


Window grilles are Clear Cypress texture. Windows not available on Designs 31, 32, 33, 34, 35, 36, 37 and 38. Double door designs also available.

Standard windows available on the following widths only: 6'2", 8'0", 9'0", 10'0", 10'2", 12'0", 12'2", 13'6", 15'0", 15'2", 15'6", 15'8", 16'0", 16'2", 18'0", 18'2", 20'0", 20'2".

Impact windows available on the following widths only: 8'0", 9'0", 10'0", 12'2", 16'2", 18'2". To view additional designs, windows and top sections available, please visit www.clopaydoor.com.

Impact rated windows available.

SPECIALTY GLASS OPTIONS



Clear



Frosted



Seeded



Obscure



Rain



Clear Polycarbonate

Windows are available insulated in clear, frosted, seeded, obscure and rain.

Impact rated windows are available in clear polycarbonate and may have a wavy appearance.

CANYON RIDGE® louver



Versatile and unique, the plantation shutter style Canyon Ridge Louver garage doors are a perfect complement to coastal beach homes or colonial estates. They can also be a standout piece on traditional exteriors or modern farmhouses. Whatever your style, these doors add “wow” factor to your home.

STYLE AND CONSTRUCTION

- 5-layer construction, 2" thick Intellicore® polyurethane insulation (R-value 18.4 – 20.4).
- Attractive beveled edge, clip-in grilles are removable for easy cleaning.
- Replaceable vinyl bottom weatherseal in a rust-resistant aluminum retainer helps seal out the elements.
- 10-ball nylon rollers for quiet operation.
- Heavy-duty 14 gauge steel hinges for long-lasting performance.

Calculated door section R-value is in accordance with DASMA TDS-163.

DOOR DESIGNS

Custom designs available, contact Clopay for availability.

SERIES 4



SERIES 5



Doors shown in Slate Finish.

WINDCODE® AVAILABILITY CHART								
Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Model CAN	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	FS +30/-32 PSF	FTDWS +38/-44 PSF	SELECT W8	FDW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL F +37.5/-40 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF TAPERED STRUT FDW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL F +37.5/-40 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF TAPERED STRUT FDW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	C-CHANNEL F +37/-37 PSF TAPERED STRUT FTDWS +38/-42 PSF		
S Standard Windows Available Impact Rated			W Patented Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved		

For W6–W8 doors over 10'2" wide, add 2" to the door opening.

CANYON RIDGE® louver



MATERIAL DESIGN OPTIONS

CLADDING/STEEL BASE MATERIAL



Louver Mahogany



Ultra-Grain® Finish Clear Cypress
or Solid Color Steel

OVERLAY MATERIAL



Clear Cypress



Mahogany

Cladding and overlay material options may be mixed and matched.

FINISHING AND CARE: Proper care and maintenance are imperative for long-term performance and appearance of Canyon Ridge® garage doors. Periodic inspection and maintenance of the composite cladding and overlays are required. Complete finishing and maintenance instructions are provided with the door and are also available from your Clopay Dealer or online at www.clopaydoor.com.

COLOR OPTIONS



Medium Finish



Dark Finish*




Walnut Finish



Slate Finish



Black Finish†



White Finish†



Primed
(No Finish)

*Dark Finish not available as a base steel color on Designs 41, 42, 43, 44, 45, 46 and 47.

†Black and White Finish available only on Mahogany cladding and overlays.

Two-tone doors are available. To see all available options go to: dis.clopay.com.

Doors can be ordered primed for those homeowners wishing to custom paint or stain their doors. Note: Primed solid steel base is a brown color. Door stain color will vary slightly within a door due to the finishing process. Due to the printing process, above colors may vary.

WINDOW OPTIONS



REC11



REC13



REC14



SQ23



SQ24

Standard windows available on the following widths only: 6'2", 8'0", 9'0", 10'0", 10'2", 12'0", 12'2", 13'6", 15'0", 15'2", 15'6", 15'8", 16'0", 16'2", 18'0", 18'2", 20'0", 20'2".

Impact windows available on the following widths only: 8'0", 9'0", 10'0", 12'2", 16'2", 18'2".


impact rated windows available.

Window grilles are Mahogany texture.
Windows available only on Louver Design 52.



Design 52 with REC11 Windows

SPECIALTY GLASS OPTIONS



Clear



Frosted



Seeded



Obscure



Rain




Clear Polycarbonate

Windows are available insulated in clear, frosted, seeded, obscure and rain.

Impact rated windows are available in clear polycarbonate and may have a wavy appearance.

COACHMAN®



Coachman® garage doors give your home classic elegance while complementing your home's architectural style.

STYLE AND CONSTRUCTION

- Custom composite overlay with beveled, coped edge and center groove creates a detailed carriage house look, available in four colors.
- Model CGU has 2" thick Intellicore® polyurethane insulation (R-value 18.4).
- Model CG has 2" thick bonded polystyrene insulation (R-value 9.0).
- Model CD has 1-3/8" thick bonded polystyrene insulation (R-value 6.5).
- Insulated with a thermal break between two layers of bonded steel.
- Coachman® garage doors can be painted using a high-quality exterior latex paint. **IMPORTANT:** For doors being painted black and very dark colors (having an LRV of 12 or less), please order Canyon Ridge® Carriage House 4-Layer in Black or primed. For colors having an LRV of 13 to 38 we require the use of tested and approved paints. A list of tested and approved paints can be found at: <http://info.garagedoors.com/lrv>. Calculated door section R-value is in accordance with DASMA TDS-163.

STEEL BASE / COMPOSITE OVERLAY COLORS




SPECIALTY GLASS OPTIONS




DOOR DESIGNS

Custom designs available, contact Clopay for availability.



WINDOW OPTIONS



WINDCODE® AVAILABILITY CHART

Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Model CD	8', 9' Wide Door	S +13/-15 PSF	SELECT W5	SELECT W5	FTS +33/-37 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25/-28 PSF				
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25/-25 PSF				
	18' Wide Door	S +12.5/-14 PSF						
Model CG	8', 9' Wide Door	S +13/-15 PSF	SELECT W6	SELECT W6	SELECT W6	FTS +38/-42 PSF C-CHANNEL FT +37.5/-40 PSF	SELECT W8	FT +54/-60 PSF C-CHANNEL FD +46.6/-52 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W5	SELECT W5	FTS +30/-30 PSF	FTS +30/-30 PSF C-CHANNEL FT +37.5/-40 PSF	SELECT W8	FTS +30/-30 PSF C-CHANNEL FD +46.6/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W5	SELECT W5	FTS +30/-30 PSF	FTS +30/-30 PSF C-CHANNEL FT +37.5/-40 PSF	SELECT W8	FTS +30/-30 PSF C-CHANNEL FD +46.6/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	FTS +37/-37 PSF C-CHANNEL FT +37.5/-40 PSF		
Model CGU	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	S +28/-29 PSF	SELECT W6	FTDWS +38/-44 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	FDW +54/-60 PSF TAPERED STRUT FD +46/-52 PSF
	10' Wide Door	S +12.5/-14 PSF	SELECT W4	S +25/-25 PSF	+30/-30 PSF	FTDWS +38/-42 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	FDW +46/-52 PSF TAPERED STRUT FDW +46/-52 PSF
	12' Wide Door	S +12.5/-14 PSF	SELECT W4	S +25/-25 PSF	+30/-30 PSF	FTDWS +38/-42 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	FDW +46/-52 PSF TAPERED STRUT FDW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	S +25/-25 PSF	+30/-30 PSF	FTDWS +38/-42 PSF TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	FDW +46/-52 PSF TAPERED STRUT FDW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	S +25/-25 PSF	SELECT W6	FTDWS +38/-42 PSF TAPERED STRUT FTDWS +38/-42 PSF		

S Standard Windows Available
I Impact Rated

W Patented Impact Windows Available
F Florida Approved

D Dade County Approved
T Texas Department of Insurance Approved

For W6-W8 doors over 10'2" wide, add 2" to the door opening.

For W1, Model CG is not available.

AVANTE®



Avante® is the perfect choice to modernize any home.

STYLE AND CONSTRUCTION


- 2-1/8" aluminum frame provides a virtually maintenance-free, long-lasting door.
- Tempered glass, acrylic or solid aluminum panel options. Insulated glass is also available for increased energy efficiency (Model AVI).
- Section joint seal helps keep out air and water (Model AX).
- Integral reinforcing fin provides increased strength and longevity (Available on all AVI and AV models and double car AX models).
- Heavy-duty steel ball bearing rollers with nylon tires provide quiet operation.

DOOR DESIGNS



Additional sizes available for commercial door configurations. Contact Clopay for details.

HARDWARE




FRAME/SOLID PANEL COLOR OPTIONS



Due to the anodizing process, color variation may occur. The use of "Bronze (Painted)" is recommended for a more consistent bronze finish color. Custom colors available.

GLASS/PANEL OPTIONS

NOTE: Glass options affect price.




*Glass is tempered. Glass available in single pane or insulated. White laminated, black laminated and mirrored glass not available insulated. Panels can be aluminum to match the aluminum frame. Glass/acrylic panels may be combined with aluminum panels. Custom glass and colors available. See your Clopay Dealer for details. Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clopaydoor.com/acrylic for complete details.

WINDCODE® AVAILABILITY CHART						
Common Door Widths		W1	W2	W3	W4	W5
Models AV/AVI	8', 9', 10', 12' Wide Door	S +16.5/-16.5 PSF	SELECT W5	SELECT W5	SELECT W5	FS +32/-32 PSF
	14' Wide Door	S +13.5/-13.5 PSF	SELECT W5	SELECT W5	SELECT W5	FS +30/-30 PSF
	16' Wide Door	SELECT W5	SELECT W5	SELECT W5	SELECT W5	FS +30/-30 PSF
	18' Wide Door	SELECT W5	SELECT W5	SELECT W5	SELECT W5	FS +30/-30 PSF
Model AX	8', 9', 10' Wide Door	S +14/-14 PSF	S +18/-20 PSF	SELECT W4	FS +25/-25 PSF	FS +30/-30 PSF
	12' Wide Door	S +14/-14 PSF	S +18/-20 PSF	SELECT W4	FS +25/-25 PSF	FS +32/-32 PSF
	14' Wide Door	S +14/-14 PSF	S +18/-20 PSF	SELECT W4	FS +25/-25 PSF	FS +32/-32 PSF
	16' Wide Door	S +14/-14 PSF	S +18/-20 PSF	SELECT W4	FS +25/-25 PSF	FS +32/-32 PSF
	18' Wide Door	S +14/-14 PSF	S +18/-20 PSF	SELECT W4	FS +25/-25 PSF	FS +30/-30 PSF
	20' Wide Door	S +14/-14 PSF	S +18/-20 PSF	SELECT W4	FS +25/-25 PSF	FS +30/-30 PSF
S Standard Windows Available W Impact Windows Available D Dade County Approved I Impact Rated F Florida Approved T Texas Department of Insurance Approved *Doors require additional center stiles/more windows per section compared to standard doors						

Glass may be obscured with reinforcement on 18' wide doors.

GALLERY® STEEL



Constructed of durable steel, this vintage style line is available in long or short grooved panel designs with various windows, colors and hardware options to create that one-of-a-kind look.

STYLE AND CONSTRUCTION

- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps ensure durability and long-lasting beauty.
- Intellicore® polyurethane or bonded polystyrene insulation with R-values ranging from 18.4 to 6.3.
- Windows are standard with double strength clear glass and have optional snap-in grilles. Other glass options are available; see opposite page for available options.
- Section joints and bottom weatherseal in a rust-resistant aluminum retainer help seal out the elements.

Calculated door section R-value is in accordance with DASMA TDS-163.

PANEL OPTIONS




Short Panel



Long Panel

COLOR OPTIONS



Due to the printing process, colors may vary.

**Not available on all models. Complete color availability can be found on page 40.*

†Popular in select markets, Glacier White is a brighter white.

‡Additional charges apply.

Ultra-Grain® finish is a faux woodgrain paint coating offering the beauty of stained wood without the upkeep.

Ultra-Grain® finish doors have stucco texture.

PANEL DETAIL

Deep-embossed panels with woodgrain or stucco (Ultra-Grain® finish only) surface texture improve appearance close-up and from the curb.



MODEL SPECIFICATIONS

MODEL	GD2SU	GD2LU	GD1SU	GD1LU	GD2SP	GD2LP	GD1SP	GD1LP
Panel Style	Short	Long	Short	Long	Short	Long	Short	Long
Insulation	2" Intellicore® Polyurethane	2" Intellicore® Polyurethane	1-3/8" Intellicore® Polyurethane	1-3/8" Intellicore® Polyurethane	2" Bonded Polystyrene	2" Bonded Polystyrene	1-3/8" Bonded Polystyrene	1-3/8" Bonded Polystyrene
Construction	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer
R-value	18.4	18.4	12.9	12.9	9.0	9.0	6.5	6.5

GALLERY® STEEL



WINDOW OPTIONS

GLASS



Plain Short



REC12



SQ22



Plain Long



REC14



SQ24



ARCH1



Vertical Grille on ARCH1



Grille on ARCH1



ARCH2



Vertical Grille on ARCH2



Grille on ARCH2



Trenton® Short*



Kristin® Short*



Clayton™ Short*



Trenton® Long*



Kristin® Long*



Clayton™ Long*

ACRYLIC



Wrought Iron Short*



Wrought Iron Long*




Wrought Iron Arch*

*Complements Clopay Entry Door glass. Additional double width door designs available. Double strength glass is standard. Long windows are available on short panel doors and short windows are available on long panel doors. Some limitations may apply based on W-Level. Contact your Clopay Dealer for details.

Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clopaydoor.com/acrylic for complete details.

Impact rated windows available (Glacier White and Mocha Brown are not available on impact windows)

SPECIALTY GLASS OPTIONS



Clear



Frosted



Seeded



Obscure




Rain



Clear Polycarbonate



Bronze Polycarbonate



Matte Polycarbonate



Pebble Polycarbonate

Windows are available single pane or insulated in clear, frosted, seeded, obscure and rain designs. Impact rated windows are available in clear, bronze, matte and pebble polycarbonate and may have a wavy appearance. Additional charges of optional glass apply.

MODEL SPECIFICATIONS

MODEL	GD4S	GD4L	GD4SV	GD4LV	GD5S	GD5SV
Panel Style	Short	Long	Short	Long	Short	Short
Insulation	Non-Insulated	Non-Insulated	Polystyrene	Polystyrene	Non-Insulated	Polystyrene
Construction	1-Layer	1-Layer	2-Layer	2-Layer	1-Layer	2-Layer
R-value	N/A	N/A	6.3	6.3	N/A	6.3

GALLERY® STEEL

WINDCODE® AVAILABILITY CHART								
Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Model GD2SU	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF	SELECT W8	FW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	TAPERED STRUT FTWS +38/-42 PSF		
Model GD2LU	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF	SELECT W8	FW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	TAPERED STRUT FTWS +38/-42 PSF		
Model GD1SU	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF	SELECT W5	S +30/-32 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	18' Wide Door	S +12.5/-14 PSF						
Model GD1LU	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF	SELECT W5	S +30/-32 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	18' Wide Door	S +12.5/-14 PSF						
Model GD2SP	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF	SELECT W8	FDW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL FS +37/-40 PSF	SELECT W8	C-CHANNEL FD +46.6/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL FS +37/-40 PSF	SELECT W8	C-CHANNEL FD +46.6/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	C-CHANNEL F +37/-37 PSF		
	20'2" Wide Door	SELECT W5	SELECT W5	SELECT W5	FS +30/-33 PSF			
Model GD2LP	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF	SELECT W8	FDW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL FS +37/-40 PSF	SELECT W8	C-CHANNEL FD +46.6/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	C-CHANNEL FS +37/-40 PSF	SELECT W8	C-CHANNEL FD +46.6/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	C-CHANNEL F +37/-37 PSF		
	20'2" Wide Door	SELECT W5	SELECT W5	SELECT W5	FS +30/-33 PSF			
Model GD1SP	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF	SELECT W5	FS +30/-32 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	18' Wide Door	S +12.5/-14 PSF						
Model GD1LP	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF	SELECT W5	FS +30/-32 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	18' Wide Door	S +12.5/-14 PSF						

GALLERY® STEEL

WINDCODE® AVAILABILITY CHART										
Common Door Widths		W1	W3	W4	W5		W6		W7	W8
GD4S 24 Gauge Pan Short	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTS +25/-25 PSF	FTS +30/-32 PSF		FTW! S* +38/-44 PSF		SELECT W8	FDW +50/-58 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF	FTS* +30/-30 PSF		C-CHANNEL FTS* +37/-41 PSF	TAPERED STRUT FWS* +38/-42 PSF	SELECT W8	FDW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF	FTS* +30/-30 PSF		C-CHANNEL FTS* +37/-41 PSF	TAPERED STRUT FWS* +38/-42 PSF	SELECT W8	FDW +46/-52 PSF
	18' Wide Door	S* +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF	SELECT W6		FS* +37/-39 PSF			
GD4SV 24 Gauge Insulated Short	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTS +25/-25 PSF	FTS +30/-32 PSF					
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF	FTS* +30/-30 PSF					
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF	FTS* +30/-30 PSF					
	18' Wide Door	S* +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF						
GD4L 24 Gauge Pan Long	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTS +25/-25 PSF	SELECT W6		FTW! S* +38/-44 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF	SELECT W6		C-CHANNEL FTS* +37/-41 PSF	TAPERED STRUT FS* +38/-42 PSF		
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF	SELECT W6		C-CHANNEL FTS* +37/-41 PSF	TAPERED STRUT FS* +38/-42 PSF		
	18' Wide Door	S* +12.5/-14 PSF	SELECT W4	FTS* +25/-25 PSF						
GD4LV 24 Gauge Insulated Long	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTS +25/-25 PSF						
	10', 12' Wide Door	S +12.5/-14 PSF								
	16' Wide Door	S +12.5/-14 PSF								
	18' Wide Door									
GD5S 25 Gauge Pan Short	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +25/-32 PSF	FS +30/-32 PSF		FS* +38/-42 PSF		F +42/-48 PSF	
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS* +24/-24.5 PSF	GD5S FS* +30/-30 or +32/-32 PSF	TAPERED STRUT GD5SSP F* +32/-37 PSF	C-CHANNEL FS* +37/-41 PSF	TAPERED STRUT FS* +36/-42 PSF		
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS* +24/-24.5 PSF	GD5S FS* +30/-30 or +32/-32 PSF	TAPERED STRUT GD5SSP F* +32/-37 PSF	C-CHANNEL FS* +37/-41 PSF	TAPERED STRUT FS* +36/-42 PSF		
	18' Wide Door	S* +12.5/-14 PSF	SELECT W4	FS* +25/-27 PSF	SELECT W6		C-CHANNEL FS* +37/-37 PSF	TAPERED STRUT FS* +36/-42 PSF		
GD5SV 25 Gauge Insulated Short	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +25/-32 PSF	FS +30/-32 PSF					
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS* +24/-24.5 PSF	GD5SV FS* +30/-30 or +32/-32 PSF	TAPERED STRUT GD5SPV F* +32/-37 PSF				
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS* +24/-24.5 PSF	GD5SV FS* +30/-30 or +32/-32 PSF	TAPERED STRUT GD5SPV F* +32/-37 PSF				
	18' Wide Door	S* +12.5/-14 PSF	SELECT W4	FS* +25/-27 PSF						
S Standard Windows Available Impact Rated				W Patented Impact Windows Available F Florida Approved				D Dade County Approved T Texas Department of Insurance Approved		

For W6–W8 doors over 9' wide, add 2" to the door opening.
For W6, Model GD4S 18' wide doors are available only at 7' high.
Standard windows are not available in Texas.

*Long window availability is limited due to reinforcement requirements.
†Impact windows are not available in Texas.

BRIDGEPORT™ STEEL




Bridgeport™ Steel garage doors combine the traditional symmetry of wood stile and rail door designs with the proven durability of Clopay's three-layer, steel construction. This provides exceptional strength and energy efficiency as well as quiet operation.

STYLE AND CONSTRUCTION

- Hot-dipped galvanized steel skin with a baked-on primer and top coat helps ensure durability and long-lasting beauty.
- 2" and 1-3/8" Intellicore® polyurethane insulation. R-values from 12.9 to 18.4.
- Windows are standard with double strength clear glass and have optional snap-in grilles. Other glass options are available; see opposite page for available options.
- Section joints and bottom weatherseal in a rust-resistant aluminum retainer help seal out the elements.

Calculated door section R-value is in accordance with DASMA TDS-163.

COLOR OPTIONS



Due to the printing process, colors may vary.

**Popular in select markets, Glacier White is a brighter white.*


†Additional charges apply.

Ultra-Grain® finish is a faux woodgrain paint coating offering the beauty of stained wood without the upkeep. Ultra-Grain® finish doors have stucco texture.

PANEL OPTIONS



Narrow



Extended

PANEL DETAIL

A true recessed stamp replicates the timeless look of a rail and stile built wood door.



MODEL SPECIFICATIONS

MODEL	BD2NU	BD2EU	BD1NU	BD1EU
Panel Style	Narrow	Extended	Narrow	Extended
Insulation	2" Intellicore® Polyurethane	2" Intellicore® Polyurethane	1-3/8" Intellicore® Polyurethane	1-3/8" Intellicore® Polyurethane
Construction	3-Layer	3-Layer	3-Layer	3-Layer
R-value	18.4	18.4	12.9	12.9

BRIDGEPORT™ STEEL



Bridgeport™ Steel Narrow Panel:
Shown in Standard White
with Plain Long Windows

WINDOW OPTIONS

GLASS



Plain Short



REC12




SQ22



Plain Long



REC14



SQ24



ARCH1



Vertical Grille on ARCH1



Grille on ARCH1



ARCH2



Vertical Grille on ARCH2



Grille on ARCH2



Trenton® Short*




Kristin® Short*



Clayton™ Short*



Trenton® Long*



Kristin® Long*



Clayton™ Long*

ACRYLIC



Wrought Iron Short*



Wrought Iron Long*




Wrought Iron Arch*

*Complements Clopay Entry Door glass.
Additional double width door designs available.
Double strength glass is standard.
Long windows are available on narrow panel doors
and short windows are available on extended panel
doors. Some limitations may apply based on
W-Level. Contact your Clopay Dealer for details.

Acrylic windows require special cleaning.
Never use products that contain ammonia or
petroleum products to clean acrylic. Please visit
www.clopaydoor.com/acrylic for complete details.

Impact rated windows available
(Glacier White and Mocha Brown are
not available on impact windows)

SPECIALTY GLASS OPTIONS



Clear



Frosted



Seeded



Obscure



Rain



Clear Polycarbonate



Bronze Polycarbonate



Matte Polycarbonate



Pebble Polycarbonate


Windows are available single pane or insulated in clear, frosted, seeded, obscure and rain designs.
Impact rated windows are available in clear, bronze, matte and pebble polycarbonate and may have a wavy appearance.
Additional charges of optional glass apply.

BRIDGEPORT™ STEEL


WINDCODE® AVAILABILITY CHART								
Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Model BD2NU	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF	SELECT W8	FW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	TAPERED STRUT FTWS +38/-42 PSF		
Model BD2EU	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF	SELECT W8	FW +54/-60 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +25.5/-25.5 PSF	FS +30/-30 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	TAPERED STRUT FW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	F +25/-25 PSF	SELECT W6	TAPERED STRUT FTWS +38/-42 PSF		
Model BD1NU	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF					
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	18' Wide Door	S +12.5/-14 PSF						
Model BD1EU	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF					
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	F +30/-30 PSF			
	18' Wide Door	S +12.5/-14 PSF						

For W6–W8 doors over 9' wide, add 2" to the door opening.
Standard windows are not available in Texas.

BRIDGEPORT™ STEEL



MODERN STEEL™



Modern Steel™ garage doors complement contemporary and mid-century modern home styles. Doors are available with or without windows and with or without grooves in the panels. All are available in multiple paint and Ultra-Grain® finishes to create the perfect look for your home.

STYLE AND CONSTRUCTION



- Intellimcore® polyurethane or bonded polystyrene insulation with R-values ranging from 18.4 to 6.5.
- Modern Flush and Grooved panels with a textured steel surface improve appearance close-up and from the curb.
- Replaceable vinyl bottom weatherseal in a rust-resistant aluminum retainer helps seal out the elements.

Calculated door section R-value is in accordance with DASMA TDS-163.

COLOR OPTIONS



PANEL OPTIONS



MODEL SPECIFICATIONS

MODELS	9202, 9201	9208†	9205	9209†	9132, 9131	9138†	9139†
Panel Style	Modern Flush	Modern Flush with Contemporary Windows	Modern Grooved	Modern Grooved with Contemporary Windows	Modern Flush	Modern Flush with Contemporary Windows	Modern Grooved with Contemporary Windows
Steel Texture*	Woodgrain	Stucco	Stucco	Stucco	Woodgrain	Stucco	Stucco
Insulation	2" Intellimcore® Polyurethane	2" Intellimcore® Polyurethane	2" Intellimcore® Polyurethane	2" Intellimcore® Polyurethane	1-3/8" Intellimcore® Polyurethane	1-3/8" Intellimcore® Polyurethane	1-3/8" Intellimcore® Polyurethane
Construction	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer
R-value	18.4	18.4	18.4	18.4	12.9	12.9	12.9

MODERN STEEL™




Modern Steel™ Modern Grooved Panel shown in Mocha Brown with Plain Short Windows down left side (from inside garage looking out)

CONTEMPORARY WINDOW ORIENTATION


When ordering contemporary window configurations please reference the examples provided to describe your desired window positions.

Note: Window configurations are described from inside the garage looking out.

Example: Windows down right side (from inside garage looking out)



View from Inside Garage



View from Outside Garage

For popular contemporary window configurations and window options see pages 24–25.

MODEL SPECIFICATIONS							
MODELS	4302, 4301	4308†	4305	4309†	4132, 4051	4138†	4F, 4F4‡
Panel Style	Modern Flush	Modern Flush with Contemporary Windows	Modern Grooved	Modern Grooved with Contemporary Windows	Modern Flush	Modern Flush with Contemporary Windows	Modern Flush
Steel Texture	Woodgrain	Stucco	Stucco	Stucco	Woodgrain	Stucco	Woodgrain
Insulation	2" Bonded Polystyrene	2" Bonded Polystyrene	2" Bonded Polystyrene	2" Bonded Polystyrene	1-3/8" Bonded Polystyrene	1-3/8" Bonded Polystyrene	Non-Insulated
Construction	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer	3-Layer	1-Layer
R-value	9.0	9.0	9.0	9.0	6.5	6.5	N/A

*Exterior steel surface on an Ultra-Grain® finish door has a woodgrain texture on Modern Steel™ doors.

†Models available only with plain, rectangular grille and square grille windows. Obscure, frosted and narrow reed glass available.

‡Model 4F utilizes 21" and 18" sections while the Model 4F4 utilizes 24" and 21" sections.

MODERN STEEL™

POPULAR CONTEMPORARY WINDOW CONFIGURATIONS

The windows shown below apply to Models 9208, 9209, 9138, 9139, 4308, 4309 and 4138. These doors utilize 24" and 21" section heights, allowing for the window options shown. 18" sections not available with windows.

Contemporary window configurations come standard with tempered glass and are available in many design options, including windows in each section and down one side, short and long windows or windows in all sections. For doors with multiple window sections, the window locations must be the same in every section.

The images below are illustrated from outside the garage.


Important Note: The ordering codes listed below are from the inside of the garage looking out, as explained on the previous page. See your Clopay dealer for more details.

The illustrations shown below show window (glazed) and/or no window (solid) locations.


SOL=Solid (no window) location GL=Glazed (window) location

Sections are numbered from the floor up to the top of the door.

SHORT WINDOW CONFIGURATIONS (Viewed from outside)




SOL-SOL-SOL-GL
Sections: 1, 2, 3, 4




SOL-SOL-SOL-SOL-SOL-SOL-SOL-GL
Sections: 1, 2, 3, 4

LONG WINDOW CONFIGURATIONS (Viewed from outside)




SOL-GL
Sections: 1, 2, 3, 4




SOL-SOL-SOL-GL
Sections: 1, 2, 3, 4


NEW! SLIM WINDOW CONFIGURATIONS (Viewed from outside)




SOL-GL
Sections: 1, 2, 3, 4




SOL-SOL-SOL-GL
Sections: 1, 2, 3, 4




GL-SOL-SOL-SOL
Sections: 1, 2, 3, 4



GL-GL-SOL-SOL-SOL-SOL-SOL-SOL-SOL
Sections: 1, 2, 3, 4




GL-SOL
Sections: 1, 2, 3, 4




GL-SOL-SOL-SOL
Sections: 1, 2, 3, 4




GL-SOL
Sections: 1, 2, 3, 4



GL-SOL-SOL-SOL
Sections: 1, 2, 3, 4



GL-SOL-SOL-GL
Sections: 3, 4



GL-GL-SOL-SOL-SOL-SOL-SOL-GL-GL
Sections: 3, 4



GL-GL
Sections: 3, 4




GL-GL-GL-GL
Sections: 3, 4



GL-GL
Sections: 3, 4



GL-GL-GL-GL
Sections: 3, 4



GL-GL-GL-GL
Sections: 1, 2, 3, 4



GL-GL-GL-GL-GL-GL-GL-GL-GL
Sections: 1, 2, 3, 4



GL-GL
Sections: 1, 2, 3, 4



GL-GL-GL-GL
Sections: 1, 2, 3, 4



GL-GL
Sections: 1, 2, 3, 4



GL-GL-GL-GL
Sections: 1, 2, 3, 4

MODERN STEEL™ WINDOW OPTIONS

CONTEMPORARY SLIM WINDOW OPTIONS

Available on These Models: 9208, 9209, 4308, 4309



378SV – Silver



378BK – Black

Contemporary Slim windows are not available impact rated.
To order Contemporary Slim windows in WindCode® products, contact customer service.

CONTEMPORARY SLIM SPECIALTY GLASS OPTIONS



Clear



Frosted

Contemporary Slim windows are available single pane or insulated in clear and frosted designs.
Clear acrylic also available.

MODERN STEEL™ WINDOW OPTIONS

DECORATIVE INSERT SERIES WINDOW OPTIONS

Available on These Models: 9201, 9131, 4301, 4051, 4F, 4F4



Plain Short



Plain Long



Charleston 508



Colonial 509



Prairie 510



Sunset 501 (4, 6, 8 or 10 panels across)



Sunset 502 (3, 6 or 9 panels across)



Sunset 503 (4 or 8 panels across)



Sunset 506 (5 or 10 panels across)



Sunset 504 (7 panels across only)



Sunset 505 (8 panels across only)



Charleston 608



Stockton 612



Prairie 610



Madison 611



Madison Arch 613



Sunset 601 (2, 3, 4 or 5 long panels across)




Sunset 603 (2 or 4 long panels across)



Sunset 605 (4 long panels across)

DECORATIVE INSERT SERIES SPECIALTY GLASS OPTIONS



Plain and Snap-In Series windows are available single pane or insulated in clear, frosted, obscure and rain designs. Clear acrylic also available. Impact rated windows are available in clear polycarbonate and may have a wavy appearance.

Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clopaydoor.com/acrylic for complete details. Window heights may vary based on section height.

Impact rated windows available (Glacier White and Mocha Brown are not available on impact windows)

CONTEMPORARY/ARCHITECTURAL SERIES WINDOW OPTIONS

Available on These Models: 9202, 9201, 9208*, 9205, 9209*, 9132, 9131, 9138*, 9139*, 4302, 4301, 4308*, 4305, 4309*, 4132, 4138*



Plain Short



Plain Long



Plain Short**



Plain Long**



REC12



REC14



SQ22



SQ24



ARCH1



ARCH2



Vertical Grille on ARCH1



Vertical Grille on ARCH2



Grille on ARCH1



Grille on ARCH2



Trenton® Short†



Trenton® Long†



Kristin® Short†



Kristin® Long†



Clayton™ Short†




Clayton™ Long†



Wrought Iron Short (Acrylic)†



Wrought Iron Long (Acrylic)†



Wrought Iron Arch (Acrylic)†

* Models available only with plain, rectangular grille and square grille windows.

** 7' high doors with impact windows utilize smaller glazing height to obscure reinforcement.

† Complements Clopay Entry Door glass.

Additional double width door designs available. Double strength glass is standard.

Contemporary/Architectural Series windows are not available on Modern Steel™ Models 4051, 4F and 4F4.

CONTEMPORARY/ARCHITECTURAL SERIES SPECIALTY GLASS OPTIONS



Contemporary/Architectural Series windows are available single pane or insulated in clear, frosted, obscure and narrow reed designs.

Impact rated windows are available in clear, bronze, matte and pebble polycarbonate and may have a wavy appearance.

Additional charges for optional glass apply.

MODERN STEEL™

WINDCODE® AVAILABILITY CHART										
Common Door Widths	W1	W2	W3	W4	W5	W6	W7	W8	W9	
Models 9202, 9205	8', 9' Wide Door S +13/-15 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	FTWS* +38/-44 PSF	SELECT W8	FW* +54/-60 PSF		
	10', 12' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTWS* +38/-42 PSF	SELECT W8	TAPERED STRUT FW* +46/-52 PSF		
	16' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTWS* +38/-42 PSF	SELECT W8	TAPERED STRUT FW* +46/-52 PSF		
	18' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTWS* +38/-42 PSF	SELECT W8			
Models 9208, 9209	8', 9' Wide Door S +13/-15 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	FWS +38/-42 PSF	SELECT W8	FDWS +54/-62 PSF		
	10', 12' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	FWS +38/-42 PSF	SELECT W8	U-BAR FDWS +50/-56 PSF		
	16' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	FWS +38/-42 PSF	SELECT W8	FDWS +46/-52 PSF		
	18' Wide Door S +12.5/-14 PSF					FWS +38/-42 PSF				
Model 9201	8', 9' Wide Door S +13/-15 PSF	SELECT W4	SELECT W4	FTS +28/-29 PSF	FS +30/-32 PSF	FTWS +38/-44 PSF	SELECT W8	FTW +48/-60 PSF		
	10', 12' Wide Door S +12.5/-14 PSF	SELECT W4	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	U-BAR FWS +37/-40 PSF TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	C-CHANNEL FW +46.6/-52 PSF TAPERED STRUT FTW +46/-52 PSF		
	16' Wide Door S +12.5/-14 PSF	SELECT W4	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	U-BAR FWS +37/-40 PSF TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	C-CHANNEL FW +46.6/-52 PSF TAPERED STRUT FTW +46/-52 PSF		
	18' Wide Door S +12.5/-14 PSF	SELECT W4	SELECT W4	FTS +24/-24.5 PSF	SELECT W6	C-CHANNEL FWS +37/-37 PSF TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46/-50 PSF TAPERED STRUT FTW +46/-50 PSF		
Model 9131	8', 9' Wide Door S +13/-15 PSF	SELECT W3	FS +20/-20 PSF	FS +25/-28 PSF	FWS +33/-37 PSF	FS +37/-37 PSF				
	10', 12' Wide Door S +12.5/-14 PSF	SELECT W3	FS +20/-21 PSF	FS +24/-26 PSF	FS +32/-32 PSF					
	16' Wide Door S +12.5/-14 PSF	SELECT W3	FS +20/-21 PSF	FS +24/-26 PSF	FS +32/-32 PSF					
	18' Wide Door S +12.5/-14 PSF	SELECT W4	SELECT W4	FS +24/-26 PSF						
Models 9132, 9138, 9139	8', 9' Wide Door S +13/-15 PSF									
	10', 12' Wide Door S +12.5/-14 PSF									
	16' Wide Door S +12.5/-14 PSF									
	18' Wide Door S +12.5/-14 PSF									
Models 4302, 4305	8', 9' Wide Door S +13/-15 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	FTWS† +38/-44 PSF	SELECT W8	FDW† +54/-60 PSF		
	10', 12' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTDWS† +38/-42 PSF	SELECT W8	TAPERED STRUT FDW† +46/-52 PSF		
	16' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTDWS† +38/-42 PSF	SELECT W8	TAPERED STRUT FDW† +46/-52 PSF		
	18' Wide Door S +12.5/-14 PSF	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTWS† +38/-42 PSF				
	20'2" Wide Door SELECT W5	SELECT W5	SELECT W5	SELECT W5	FS +30/-33 PSF					

MODERN STEEL™

WINDCODE® AVAILABILITY CHART																	
Common Door Widths		W1	W2	W3	W4	W5	W6		W7	W8		W9					
Models 4308, 4309	8', 9' Wide Door	S +13/-15 PSF															
	10', 12' Wide Door	S +12.5/-14 PSF															
	16' Wide Door	S +12.5/-14 PSF															
	18' Wide Door	S +12.5/-14 PSF															
Model 4301	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	SELECT W4	FTWS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF		SELECT W8	FTW +48/-60 PSF							
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	SELECT W4	FTWS +25.5/-25.5 PSF	SELECT W6	C-CHANNEL FWS +37/-40 PSF	TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL FDW +46.6/-52 PSF	TAPERED STRUT FTDW +46/-52 PSF						
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	SELECT W4	FTWS +25.5/-25.5 PSF	SELECT W6	C-CHANNEL FWS +37/-40 PSF	TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FTDW +46/-52 PSF						
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	SELECT W4	FTWS +25/-25 PSF	SELECT W6	C-CHANNEL FWS +37/-37 PSF	TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46/-50 PSF	TAPERED STRUT FTDW +46/-50 PSF						
	20'2" Wide Door	SELECT W5	SELECT W5	SELECT W5	SELECT W5	FS +30/-33 PSF	TAPERED STRUT FTW +37/-40 PSF										
Model 4132	8', 9' Wide Door	S +13/-15 PSF															
	10', 12' Wide Door	S +12.5/-14 PSF															
	16' Wide Door	S +12.5/-14 PSF															
	18' Wide Door	S +12.5/-14 PSF															
Model 4138	8', 9' Wide Door	S +13/-15 PSF															
	10', 12' Wide Door	S +12.5/-14 PSF															
	16' Wide Door	S +12.5/-14 PSF															
	18' Wide Door	S +12.5/-14 PSF															
Model 4051	8', 9' Wide Door	S +13/-15 PSF	SELECT W3	FS +20/-21 PSF	SELECT W6	SELECT W6	FS +37/-37 PSF	FS +38/-42 PSF									
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W3	FS +20/-21 PSF	SELECT W5	FS +30/-30 PSF or +32/-32 PSF											
	16' Wide Door	S +12.5/-14 PSF	SELECT W3	FS +20/-21 PSF	SELECT W5	FS +30/-30 PSF or +32/-32 PSF											
	18' Wide Door	S +12.5/-14 PSF															
Model 4F	8', 9' Wide Door	SELECT W8	SELECT W8	SELECT W8	SELECT W8	SELECT W8	SELECT W8		SELECT W8	FW ¹ +48/-54 or +54/-62 PSF		FDW +62/-72 PSF					
	10', 12' Wide Door	SELECT W6	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTDWS* +38/-42 PSF		FDW +42/-48 PSF	C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FDW +46/-50 PSF						
	16' Wide Door	SELECT W6	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTDWS* +38/-42 or +36/-42 PSF		SELECT W8	C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FDW +46/-50 PSF						
	18' Wide Door	SELECT W6	SELECT W6	SELECT W6	SELECT W6	SELECT W6	TAPERED STRUT FTDWS* +36/-42 PSF		TAPERED STRUT FDW +41/-46 PSF								
Model 4F4	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	SELECT W4	FS +25/-25 PSF												
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	SELECT W4	FS +25/-25 PSF												
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	SELECT W4	FS +25/-25 PSF												
S Standard Windows Available Impact Rated												W Patented Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved		


For W6–W8 doors over 9' wide, add 2" to the door opening.
Standard windows are not available in Texas.

* Model 9205 is not Texas approved.

† Model 4305 is not Florida, Dade or Texas approved.

CLASSIC™ STEEL

PREMIUM




3-layer, steel construction features Intellicore® polyurethane or bonded polystyrene insulation sandwiched between two layers of heavy-duty steel for excellent energy efficiency, strength, durability and quietest operation.

STYLE AND CONSTRUCTION

- 3-layer construction (steel + insulation + steel).
- Tongue-and-groove section joint and bottom weatherseal in a rust-resistant aluminum retainer help seal out the elements.
- Woodgrain embossed, insulated steel base door painted front and back for a clean appearance.
- Prepainted Standard White end stiles and interior steel backing for a clean appearance.
- R-values range from 18.4 to 6.5.

Calculated door section R-value is in accordance with DASMA TDS-163.

COLOR OPTIONS



PANEL OPTIONS



Elegant Short (9200, 9130, 4300, 4050)



Elegant Long (9203, 9133, 4310, 4053)

PANEL DETAIL

Decorative panel edging and natural embossed woodgrain or stucco (Ultra-Grain® finish only) texture improve appearance close-up and from the curb.



MODEL SPECIFICATIONS

MODEL	9200, 9203	9130, 9133	4300, 4310	4050, 4053
Panel Style	Elegant Short and Long	Elegant Short and Long	Elegant Short and Long	Elegant Short and Long
Insulation	2" Intellicore® Polyurethane	1-3/8" Intellicore® Polyurethane	2" Bonded Polystyrene	1-3/8" Bonded Polystyrene
Construction	3-Layer	3-Layer	3-Layer	3-Layer
R-value	18.4	12.9	9.0	6.5

CLASSIC™ STEEL PREMIUM WINDOW OPTIONS

DECORATIVE INSERT SERIES WINDOW OPTIONS

Available on These Models: 9200*, 9203, 9130*, 9133, 4300*, 4310, 4050*, 4053



Plain Short



Plain Long



Charleston 508



Colonial 509



Prairie 510



Sunset 501 (4, 6, 8 or 10 panels across)



Sunset 502 (3, 6 or 9 panels across)



Sunset 503 (4 or 8 panels across)



Sunset 506 (5 or 10 panels across)



Sunset 504 (7 panels across only)



Sunset 505 (8 panels across only)



Charleston 608



Stockton 612



Prairie 610



Madison 611



Madison Arch 613



Sunset 601 (2, 3, 4 or 5 long panels across)



Sunset 603 (2 or 4 long panels across)



Sunset 605 (4 long panels across)

DECORATIVE INSERT SERIES SPECIALTY GLASS OPTIONS



Clear



Frosted



Obscure



Rain



Clear Polycarbonate

Plain and Snap-In Series windows are available single pane or insulated in clear, frosted, obscure and rain designs. Clear acrylic also available. Impact rated windows are available in clear polycarbonate and may have a wavy appearance.

Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clopaydoor.com/acrylic for complete details. Window heights may vary based on section height.



Impact rated windows available
(Glacier White and Mocha Brown are not available on impact windows)

ARCHITECTURAL SERIES WINDOW OPTIONS

Available on These Models: 9200*, 9203, 9130*, 9133, 4300*, 4310



Plain Short



Plain Long



REC12



REC14



SQ22



SQ24



ARCH1



ARCH2



Vertical Grille on ARCH1



Vertical Grille on ARCH2



Grille on ARCH1



Grille on ARCH2



Trenton® Short**



Trenton® Long**



Kristin® Short**



Kristin® Long**



Clayton™ Short**



Clayton™ Long**




Wrought Iron Short (Acrylic)**



Wrought Iron Long (Acrylic)**



Wrought Iron Arch (Acrylic)**



** Complements Clopay Entry Door glass.

Additional double width door designs available. Double strength glass is standard.

ARCHITECTURAL SERIES SPECIALTY GLASS OPTIONS



Clear



Frosted



Seeded




Obscure



Rain




Clear Polycarbonate



Bronze Polycarbonate



Matte Polycarbonate



Pebble Polycarbonate

Architectural Series windows are available single pane or insulated in clear, frosted, seeded, obscure and rain designs. Impact rated windows are available in clear, bronze, matte and pebble polycarbonate and may have a wavy appearance.

Additional charges for optional glass apply.

CLASSIC™ STEEL

PREMIUM


WINDCODE® AVAILABILITY CHART										
Common Door Widths		W1	W3	W4	W5	W6		W7	W8	
Model 9200	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTS +28/-29 PSF	FS +30/-32 PSF	FTWS +38/-44 PSF		SELECT W8	FTW +48/-60 PSF	
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	U-BAR FWS +37/-40 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FTW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	U-BAR FWS +37/-40 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FTW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +24/-24.5 PSF	SELECT W6	C-CHANNEL FWS +37/-37 PSF	TAPERED STRUT FTWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46/-50 PSF	TAPERED STRUT FTW +46/-50 PSF
Model 9203	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTS +28/-29 PSF	FS +30/-32 PSF	FTS +38/-44 PSF		SELECT W8	FT +48/-60 PSF	
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	U-BAR FS +37/-40 PSF	TAPERED STRUT FTS +38/-42 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF	TAPERED STRUT FT +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	U-BAR FS +37/-40 PSF	TAPERED STRUT FTS +38/-42 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF	TAPERED STRUT FT +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +24/-24.5 PSF	SELECT W6	C-CHANNEL FS +37/-37 PSF	TAPERED STRUT FTS +38/-42 PSF	SELECT W8	C-CHANNEL F +46/-50 PSF	TAPERED STRUT FT +46/-50 PSF
Model 9130	8', 9' Wide Door	S +13/-15 PSF	FS +20/-20 PSF	FS +25/-28 PSF	FWS +33/-37 PSF	FS +37/-37 PSF				
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	FS +24/-26 PSF	FWS +32/-32 PSF					
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	FS +24/-26 PSF	FWS +32/-32 PSF					
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +24/-26 PSF						
Model 9133	8', 9' Wide Door	S +13/-15 PSF	FS +20/-20 PSF	FS +25/-28 PSF	FS +33/-37 PSF	FS +37/-37 PSF				
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	FS +24/-26 PSF	FS +32/-32 PSF					
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	FS +24/-26 PSF	FS +32/-32 PSF					
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	FS +24/-26 PSF						
Model 4300	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTWS +28/-29 PSF	SELECT W6	FTWS +38/-44 PSF		SELECT W8	FTDW +48/-60 PSF	
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTWS +25.5/-25.5 PSF	SELECT W6	C-CHANNEL FWS +37/-40 PSF	TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL FDW +46.6/-52 PSF	TAPERED STRUT FTDW +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTWS +25.5/-25.5 PSF	SELECT W6	C-CHANNEL FWS +37/-40 PSF	TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FTDW +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	FTWS +25/-25 PSF	SELECT W6	C-CHANNEL FWS +37/-37 PSF	TAPERED STRUT FTDWS +38/-42 PSF	SELECT W8	C-CHANNEL F +46/-50 PSF	TAPERED STRUT FTDW +46/-50 PSF
	20'2" Wide Door	SELECT W5	SELECT W5	SELECT W5	FS +30/-33 PSF	TAPERED STRUT FTW +37/-40 PSF				
Model 4310	8', 9' Wide Door	S +13/-15 PSF	SELECT W4	FTS +28/-29 PSF	SELECT W6	FTS +38/-44 PSF		SELECT W8	FDT +48/-60 PSF	
	10', 12' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	C-CHANNEL FS +37/-40 PSF	TAPERED STRUT FTDS +38/-42 PSF	SELECT W8	C-CHANNEL FD +46.6/-52 PSF	TAPERED STRUT FTD +46/-52 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25.5/-25.5 PSF	SELECT W6	C-CHANNEL FS +37/-40 PSF	TAPERED STRUT FTDS +38/-42 PSF	SELECT W8	C-CHANNEL F +46.6/-52 PSF	TAPERED STRUT FTD +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	FTS +25/-25 PSF	SELECT W6	C-CHANNEL FS +37/-37 PSF	TAPERED STRUT FTDS +38/-42 PSF	SELECT W8	C-CHANNEL F +46/-50 PSF	TAPERED STRUT FTD +46/-50 PSF
	20'2" Wide Door	SELECT W5	SELECT W5	SELECT W5	F +30/-33 PSF	TAPERED STRUT FTW +37/-40 PSF				
Model 4050	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF	SELECT W6	SELECT W6	FS +37/-37 PSF	FWS +38/-42 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	FWS +30/-30 PSF or +32/-32 PSF					
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	FWS +30/-30 PSF or +32/-32 PSF					
	18' Wide Door	S +12.5/-14 PSF								
Model 4053	8', 9' Wide Door	S +13/-15 PSF	FS +20/-21 PSF	SELECT W6	SELECT W6	FS +37/-37 PSF	FWS +38/-42 PSF			
	10', 12' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	FWS +30/-30 PSF or +32/-32 PSF					
	16' Wide Door	S +12.5/-14 PSF	FS +20/-21 PSF	SELECT W5	FWS +30/-30 PSF or +32/-32 PSF					
	18' Wide Door	S +12.5/-14 PSF								
S Standard Windows Available Impact Rated										
W Patented Impact Windows Available F Florida Approved										
D Dade County Approved T Texas Department of Insurance Approved										

For W6-W8 doors over 9' wide, add 2" to the door opening.

Standard windows are not available in Texas.

CLASSIC™ STEEL

VALUE PLUS (builder grade)



MODEL SPECS			
MODELS	76V/76VSP	94V	1500/15SP
Panel Styles	Long	Short	Short
Section Joint	Shiplap	Shiplap	Shiplap
Steel Gauge	25	24	25
Insulation Thickness	1-5/16"	1-5/16"	1-5/16"

Heavy-duty, 2-layer steel construction with insulation for added comfort, energy efficiency and quiet operation.

STYLE AND CONSTRUCTION

- 2-layer construction (steel + vinyl-backed polystyrene insulation).
- Woodgrain embossed, insulated steel base door painted front and back for a virtually maintenance-free door.
- Quality 24 or 25 gauge steel and 2" thick frame construction for durability and longevity.
- Vinyl-backed insulation for a clean interior appearance.
- Polystyrene insulation: R-value 6.3.

Calculated door section R-value is in accordance with DASMA TDS-163.

PANEL OPTIONS



COLOR OPTIONS



Due to the printing process, colors may vary.

WINDCODE® AVAILABILITY CHART											
Common Door Widths		W1**	W2	W3	W4		W5				
USE T52											
Models 1500/15SP	8', 9' Wide Door	 +13/-15 PSF	 +16/-18.5 PSF	 +20/-21 PSF	 +25/-32 PSF		1500 +30/-32 PSF	15SP	 +32/-37 PSF		
	10', 12' Wide Door	 +12.5/-14 PSF	 +15.5/-17 PSF	 +20/-21 PSF	 +24/-24.5 PSF		1500 +30/-30 or +28/-30.5 or +32/-32 PSF	15SP +32/-37 PSF	15SP	 +32/-37 PSF	
	16' Wide Door	 +12.5/-14 PSF	 +15.5/-17 PSF	 +20/-21 PSF	 +24/-24.5 PSF		1500 +30/-30 or +28/-30.5 or +32/-32 PSF	15SP +32/-37 PSF	15SP	 +32/-37 PSF	
	18' Wide Door	 +12.5/-14 PSF	SELECT W4	SELECT W4	1500 +25/-25 PSF	1500 +25/-27 PSF					
Model 94V	8', 9' Wide Door	 +13/-15 PSF	 +16/-18.5 PSF	 +20/-21 PSF	 +25/-32 PSF		 +30/-32 PSF				
	10', 12' Wide Door	 +12.5/-14 PSF	 +15.5/-17 PSF	 +20/-21 PSF	 +24/-24.5 PSF		 +30/-30 or +28/-30.5 or +32/-32 PSF				
	16' Wide Door	 +12.5/-14 PSF	 +15.5/-17 PSF	 +20/-21 PSF	 +24/-24.5 PSF		 +30/-30 or +28/-30.5 or +32/-32 PSF				
	18' Wide Door	 +12.5/-14 PSF	SELECT W4	SELECT W4	 +25/-25 PSF						
Models 76V/76VSP	8', 9' Wide Door	 +13/-15 PSF	SELECT W4	SELECT W4	 +25/-32 PSF		76V +30/-32 PSF	76VSP	 +32/-37 PSF		
	10', 12' Wide Door	 +12.5/-14 PSF	SELECT W5	SELECT W5	SELECT W5		SELECT W5	76VSP +32/-37 PSF	76VSP	 +32/-37 PSF	
	16' Wide Door	 +12.5/-14 PSF	SELECT W5	SELECT W5	SELECT W5		SELECT W5	76VSP +32/-37 PSF	76VSP	 +32/-37 PSF	
	18' Wide Door	 +12.5/-14 PSF									
Standard Windows Available Impact Rated		Patented Impact Windows Available Florida Approved			Dade County Approved Texas Department of Insurance Approved						

For W6-W8 doors over 9' wide, add 2" to the door opening.

**Long window availability is limited due to reinforcement requirements.*

***For W1, Model T52 is used. Model T52 is a tongue-and-groove, 2-layer door.*

**Impact windows are not available in Texas.*

CLASSIC™ STEEL

VALUE (builder grade)



MODEL SPECS			
MODELS	73	76	94
Panel Styles	Traditional Short	Traditional Long	Traditional Short
Steel Gauge	25	25	24
Insulation Thickness	N/A	N/A	N/A

Single-layer, non-insulated steel construction provides beauty and durability at an economical value.

STYLE AND CONSTRUCTION

- 1-layer construction (steel).
- Woodgrain embossed steel base door painted front and back for a virtually maintenance-free door.
- Quality 24 or 25 gauge steel and 2" thick frame construction for durability and longevity.
- Woodgrain textured short and long raised panel designs in 1-layer construction complement traditional home styles.

PANEL OPTIONS



Traditional Short (73, 94)



Traditional Long (76)

COLOR OPTIONS



Due to the printing process, colors may vary.

WINDCODE® AVAILABILITY CHART													
Common Door Widths		W1**	W2	W3	W4	W5	W6		W7		W8		W9
USE T50													
Model 94	8', 9' Wide Door	S +13/-15 PSF	S +16/-18.5 PSF	FS +20/-21 PSF	FTWS +25/-32 PSF	FTWS +30/-32 PSF	FTWS* +38/-42 PSF		FDW +42/-48 PSF		FW† +48/-54 or +54/-62 PSF		FDW +62/-72 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	S +15.5/-17 PSF	FS +20/-21 PSF	FTWS* +24/-24.5 PSF	FTWS +30/-30 or +28/-30.5 or +32/-32 PSF	C-CHANNEL FWS* +37/-41 PSF	TAPERED STRUT FTDWS* +38/-42 PSF	FW +42/-48 PSF		C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FDW +46/-50 PSF	
	16' Wide Door	S +12.5/-14 PSF	S +15.5/-17 PSF	FS +20/-21 PSF	FTWS* +24/-24.5 PSF	FTWS +30/-30 or +28/-30.5 or +32/-32 PSF	C-CHANNEL FWS* +37/-41 PSF	TAPERED STRUT FTDWS* +38/-42 or +36/-42 PSF	FW +42/-48 PSF		C-CHANNEL FW +46.6/-52 PSF	TAPERED STRUT FDW +46/-50 PSF	
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	SELECT W4	FTWS* +25/-25 PSF	SELECT W6	C-CHANNEL FWS* +37/-37 PSF	TAPERED STRUT FTDWS* +36/-42 PSF	C-CHANNEL FW +42/-46 PSF	TAPERED STRUT FDW +41/-46 PSF			

CLASSIC™ STEEL
VALUE (builder grade)



WINDCODE® AVAILABILITY CHART													
Common Door Widths		W1**	W2	W3	W4		W5			W6		W7	W8
USE T50													
Models 73/73SP	8', 9' Wide Door	S +13/-15 PSF	S +16/-18.5 PSF	FS +20/-21 PSF	FTW [†] S +25/-32 PSF		73 FTW [†] S +30/-32 PSF		73SP FWS +32/-37 PSF		FTWS +38/-44 PSF	FW +42/-48 PSF	FW +46/-50 PSF
	10', 12' Wide Door	S +12.5/-14 PSF	S +15.5/-17 PSF	FS +20/-21 PSF	FTW [†] S +24/-24.5 PSF		73 FTW [†] S +28/-30.5 or +30/-30 or +32/-32 PSF		C-CHANNEL 73SP FWS +32/-37 PSF	TAPERED STRUT 73SP FWS +32/-37 PSF	C-CHANNEL FWS +37/-41 PSF	TAPERED STRUT FTWS +36/-42 PSF	C-CHANNEL FW +42/-48 PSF
	16' Wide Door	S +12.5/-14 PSF	S +15.5/-17 PSF	FS +20/-21 PSF	FTW [†] S +24/-24.5 PSF		73 FTW [†] S +28/-30.5 or +30/-30 or +32/-32 PSF		C-CHANNEL 73SP FWS +32/-37 PSF	TAPERED STRUT 73SP FWS +32/-37 PSF	C-CHANNEL FWS +37/-41 PSF	TAPERED STRUT FTWS +36/-42 PSF	C-CHANNEL FW +42/-48 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	SELECT W4	C-CHANNEL 73 FTW [†] S +25/-25 PSF	TAPERED STRUT 73 FTW [†] S +25/-27 PSF	SELECT W6				C-CHANNEL FWS +37/-37 PSF	TAPERED STRUT FTWS +36/-42 PSF	
Models 76/76SP	8', 9' Wide Door	S +13/-15 PSF	S +16/-18.5 PSF	FS +20/-21 PSF	FTW [†] S +25/-32 PSF		76 FT +30/-32 PSF		76SP F +32/-37 PSF		FT +38/-44 PSF		
	10', 12' Wide Door	S +12.5/-14 PSF	S +15.5/-17 PSF	FS +20/-21 PSF	FTW [†] S +24/-24.5 PSF		76 FT +28/-30.5 or +30/-30 or +32/-32 PSF		C-CHANNEL 76SP F +32/-37 PSF	TAPERED STRUT 76SP F +32/-37 PSF	C-CHANNEL F +37/-41 PSF	TAPERED STRUT F +36/-42 PSF	
	16' Wide Door	S +12.5/-14 PSF	S +15.5/-17 PSF	FS +20/-21 PSF	FTW [†] S +24/-24.5 PSF		76 FT +28/-30.5 or +30/-30 or +32/-32 PSF		C-CHANNEL 76SP F +32/-37 PSF	TAPERED STRUT 76SP F +32/-37 PSF	C-CHANNEL F +37/-41 PSF	TAPERED STRUT F +36/-42 PSF	
	18' Wide Door	+12.5/-14 PSF	SELECT W4	SELECT W4	C-CHANNEL 76 FTW [†] S +25/-25 PSF	TAPERED STRUT 76 FTW [†] S +25/-27 PSF							
S Standard Windows Available FTW [†] Impact Rated													
W Patented Impact Windows Available F Florida Approved													
D Dade County Approved T Texas Department of Insurance Approved													

For W6–W8 doors over 9' wide, add 2" to the door opening.

For W6, Model 76 doors are not available over 16'2" wide.

*Long window availability is limited due to reinforcement requirements.

**For W1, Model T50 is used. Model T50 is a tongue-and-groove, 1-layer door.

†Impact windows available at +48/-54 PSF.

*Impact windows not available in Texas.

CLASSIC™ STEEL

VALUE PLUS & VALUE



Value Traditional Short Panel with
Prairie 510 Window Design shown in Standard White

WINDOW OPTIONS

DECORATIVE INSERT SERIES

Available on These Models: 73, 73SP, 76, 76SP, 76V, 76VSP, 94, 94V, 1500, 15SP



Plain Short



Plain Long



Charleston 508



Colonial 509



Prairie 510



Sunset 501 (4, 6, 8 or 10 panels across)



Sunset 502 (3, 6 or 9 panels across)



Sunset 503 (4 or 8 panels across)



Sunset 504 (7 panels across only)



Sunset 505 (8 panels across only)



Sunset 506 (5 or 10 panels across)



Charleston 608



Prairie 610



Stockton 612



Madison 611



Madison Arch 613



Sunset 601 (2, 3, 4 or 5 long panels across)



Sunset 603 (2 or 4 long panels across)



Sunset 605 (4 long panels across)

SPECIALTY GLASS OPTIONS



Clear



Frosted



Obscure



Rain



Clear
Polycarbonate

Plain and Snap-In Series windows are available single pane or insulated in clear, frosted, obscure and rain designs.

Clear acrylic also available.

Impact rated windows are available in clear polycarbonate and may have a wavy appearance. Additional charges for optional glass apply.

Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clogaydoor.com/acrylic for complete details.

Window heights may vary based on section height.

 Impact rated windows available
(Glacier White and Mocha Brown are not available on impact windows)

GRAND HARBOR®

(builder grade)

HANDCRAFTED 3 OR 2-LAYER CONSTRUCTION



When budget is the deciding factor, this low maintenance, insulation-optional steel frame, carriage house style garage door combines clean lines and classic charm to provide a popular style at a great value. Accented with decorative black wrought iron hardware, these doors have the appearance of a swing-out door, but offer the convenience of modern overhead operation.

STYLE AND CONSTRUCTION


- Woodgrain embossed 24 gauge, 2" steel frame construction with 1/2" smooth composite overlay creates authentic carriage house styling.
- Model GH is non-insulated.
- Model GHV has 1-5/8" vinyl-backed insulation that improves energy efficiency with a 6.3 R-value.
- Available in 8 different designs.
- Window options include square, rectangular and arch windows with removable grilles. Glazing includes DSB clear or obscure glass and acrylic wrought iron designs. Unique faux window top sections are also an option.

Calculated door section R-value is in accordance with DASMA TDS-163.


COLOR OPTIONS



DOOR DESIGNS



WINDOW OPTIONS



Acrylic windows require special cleaning. Never use products that contain ammonia or petroleum products to clean acrylic. Please visit www.clopaydoor.com/acrylic for complete details.

WINDCODE® AVAILABILITY CHART								
Common Door Widths	W1	W3	W4	W5	W6	W7	W8	
Grand Harbor®	8', 9' Wide Door	S +12/-15 PSF	SELECT W4	FS +25/-32 PSF	FS* +30/-32 PSF	FTS* +38/-44 PSF	SELECT W8	FD +50/-58 PSF
	16' Wide Door	S +12.5/-14 PSF	SELECT W4	FS* +24/-24.5 PSF	FS* +30/-30 PSF	C-CHANNEL FTS* +37/-41 PSF	SELECT W8	FD +46/-52 PSF
	18' Wide Door	S +12.5/-14 PSF	SELECT W4	FS* +25/-25 PSF				
S Standard Windows Available Impact Rated			W Impact Windows Available Florida Approved		D Dade County Approved T Texas Department of Insurance Approved			


For W6-W8 doors over 9' wide, add 2" to the door opening.

*Long window availability is limited due to reinforcement requirements.

RESERVE® WOOD

LIMITED EDITION

HANDCRAFTED 5 OR 4-LAYER CONSTRUCTION



Distinguish your home with Clopay's Reserve® Wood Limited Edition garage doors, a line of eight polystyrene insulated wood door styles based on the most inspired (and requested) custom designs.

STYLE AND CONSTRUCTION

- Doors are available in 8 designs with 13 window/top section styles.
- Standard and optional decorative hardware available.
- Handcrafted, 5 or 4-layer construction, polystyrene insulated wood door with a 5.9 R-value.
- 1/4" thick, imported hardwood interior backer glued to stiles and rails.
- Tongue-and-groove section joint.
- All doors can be factory primed or finish painted White. Factory stain available for stained grade wood species.

Calculated door section R-value is in accordance with DASMA TDS-163.


SPECIALTY GLASS OPTIONS



Windows are single pane and double strength 1/8" thick. Additional charges for optional glass apply.

DOOR DESIGNS

Doors shown 8' wide x 7' high.



WINDOW OPTIONS




Double door designs also available.

MATERIAL OPTIONS

OVERLAYS



BASE FACE MATERIALS



**Extra® wood doors cannot be stained.*

***On Tongue-and-Groove (T&G) base doors, the wood species must match overlay species.*

WINDCODE® AVAILABILITY CHART


Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Limited Edition	8', 9' Wide Door	S +13/-15 PSF	SELECT W6	SELECT W6	SELECT W6	FS +39/-45 PSF		FDW +47/-55 PSF
	10', 12' Wide Door	S +12.5/-14 PSF					FW +41/-48 PSF	
	16' Wide Door	S +12.5/-14 PSF					FW +41/-48 PSF	
	18' Wide Door							
S Standard Windows Available Impact Rated			W Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved		

For W6-W8 doors over 9' wide, add 2" to the door opening.

RESERVE® WOOD

MODERN

HANDCRAFTED 4-LAYER CONSTRUCTION



Clean lines and simple forms let the beauty of natural wood stand out. The versatile Reserve® Wood Modern garage doors let you mix materials, shape and tone to create a stunning contemporary garage door that blends beautifully with other woods and materials on your exterior.

STYLE AND CONSTRUCTION

- Handcrafted, 4-layer construction, polystyrene insulated wood door with a 5.9 R-value.
- Built with a sleek contemporary style and convenient upward-acting operation.
- Offset Window models feature a variety of short and long window options that come standard with clear tempered glass.
- Accent Strip models feature decorative flush aluminum accent strips to provide a beautiful contrast of materials. The result is a look that is modern as well as elegant.
- Heavy-duty hinges, rollers and track provide smooth, quiet, long-lasting operation.
- Replaceable vinyl bottom weatherseal in a rust-resistant aluminum retainer helps seal out the elements.
- All doors can be factory primed or finish painted white. Factory stain available for stained grade wood species.

Calculated door section R-value is in accordance with DASMA TDS-163.

DOOR DESIGNS

Doors shown 8' wide x 7' high.



Accent Strip and Horizontal Cladding models are available spliced and unspliced. Unspliced models are available up to 10' wide.

OFFSET WINDOW DESIGNS



Note: All designs shown are illustrated from the exterior of the garage. Door designs must be ordered based on the view from the interior of the garage.

*All right-hand designs are shown. Designs 1, 3, 5 and 6 are also available left-handed. *Not available 10'1" to 13'6". Special order only.*

SPECIALTY GLASS OPTIONS



Windows are single pane and double strength 1/8" thick. Additional charges for optional glass apply.

MATERIAL OPTIONS




WINDCODE® AVAILABILITY CHART

Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Modern	8', 9' Wide Door	S +13/-15 PSF	SELECT W6	SELECT W6	SELECT W6	FS +39/-45 PSF		FD +47/-55 PSF
	10', 12' Wide Door	S +12.5/-14 PSF					F +41/-48 PSF	
	16' Wide Door	S +12.5/-14 PSF					F +41/-48 PSF	
	18' Wide Door							
S Standard Windows Available Ⓢ Impact Rated			W Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved		

For W6-W8 doors over 9' wide, add 2" to the door opening.

RESERVE® WOOD

SEMI-CUSTOM



Just because your garage door is a standard size doesn't mean it deserves a standard, cookie-cutter door. That's why Clopay has created its Reserve® Wood Semi-Custom garage doors. These upward-acting wood doors operate just like conventional, modern garage doors.

STYLE AND CONSTRUCTION

- Handcrafted, 2-layer wood doors. Swing-out appearance – modern operation.
- Semi-Custom available in 6 door designs and 10 window or top sections for multiple door design options.
- Windows are single pane and double strength 1/8" thick.
- Premium grade hardware, rollers and track assure smooth, quiet, long-lasting operation.


SPECIALTY GLASS OPTIONS



Additional charges for optional glass apply.

DOOR DESIGNS

Doors shown 8' wide x 7' high.



WINDOW OPTIONS



Double door designs also available.

MATERIAL OPTIONS



Differences in grain and color variations are indicative of natural wood.

Paint grade and grooved doors cannot be stained.

WINDCODE® AVAILABILITY CHART								
Common Door Widths		W1	W3	W4	W5	W6	W7	W8
Semi-Custom	8', 9' Wide Door	S +13/-15 PSF	SELECT W5	SELECT W5	F S +32/-36 PSF			
	10', 12' Wide Door	S +12/-14 PSF	SELECT W5	SELECT W5	F S* +30/-33.3 PSF			
	16' Wide Door	S +12/-14 PSF	SELECT W5	SELECT W5	F S* +30/-33.3 PSF			
	18' Wide Door							
S Standard Windows Available I Impact Rated			W Impact Windows Available F Florida Approved			D Dade County Approved T Texas Department of Insurance Approved		

*Available only in Hemlock.

RESERVE® WOOD

FACTORY FINISHES




Clopay stain-grade wood doors of any species are available in nine beautiful stain colors. Custom stain and paint color finishes are available upon request. See your Clopay Dealer for the Clopay Stain Color brochure or to view stained wood samples in person.



*Note: Printed colors shown here may vary from actual product colors. Clopay stain colors shown on Hemlock wood.
Custom colors are available.

3-LAYER STAIN PROCESS



3-LAYER PAINT PROCESS



WOOD DOOR CARE

- Proper care and maintenance are imperative to the appearance, longevity and performance of all wood doors.
- Doors must be painted or stained on all six sides prior to installation. Failure to follow the installation and maintenance instructions will void the warranty.
- Please refer to the installation and maintenance manual or go to www.clopaydoor.com for additional information about caring for a wood door.

PRODUCT SELECTION CHART

Garage Door	Type	Model/Design	Door/Panel Style	Sect. Hts.	Construction/Material	Colors
Avante®		AX with Section Joint Seal AV/AV Legacy Model	Contemporary	18", 21", 24"	Aluminum Frame + Glass/Acrylic Panels Aluminum Frame + Aluminum Panels	Clear Aluminum Anodized, Standard White, Bronze Painted, Chocolate Painted, Bronze Anodized, Black Anodized, Dark Bronze Anodized or Powder Coated Custom Colors
Canyon Ridge®	Carriage House 5-Layer	15 Door Designs, 14 Window or Solid Top Section Designs	Carriage House	18", 21", 24"	5 Layers: Clear Cypress, Mahogany and Pocky Cypress textures; Steel + 2" Intellcore® Polyurethane Insulation + Steel + Cladding + Overlay ¹	Medium Finish, Dark Finish, Walnut Finish, Slate Finish, Black Finish, White Finish, Primed (for those wishing to custom paint or stain their door)
Canyon Ridge®	Carriage House 4-Layer	14 Door Designs, 14 Window or Solid Top Section Designs	Carriage House	18", 21", 24"	4 Layers: Clear Cypress, Mahogany and Ultra-Grain® Solid Steel textures; Steel + 2" Intellcore® Polyurethane Insulation + Steel + Overlay ¹	Ultra-Grain® Cypress: Medium, Walnut and Slate Finishes, Black Finish, White Finish, Primed (for those wishing to custom paint or stain their door)
Canyon Ridge®	Louver	12 Door Designs, 6 Window or Solid Top Section Designs	Plantation Shutter	18", 21", 24"	5 Layers: Clear Cypress, Mahogany; Ultra-Grain® Solid Steel and Lower Mahogany textures; Steel + 2" Intellcore® Polyurethane Insulation + Steel + Cladding + Overlay ¹	Medium Finish, Dark Finish, Walnut Finish, Slate Finish, Black Finish, White Finish, Primed (for those wishing to custom paint or stain their door)
Canyon Ridge®	Modern	3 Door Designs	Contemporary	18", 21", 24"	4 Layers: Clear Cypress and Mahogany textures; Steel + 2" Intellcore® Polyurethane Insulation + Steel + Cladding or Overlay ¹	Medium Finish, Dark Finish, Walnut Finish, Slate Finish, Black Finish, White Finish, Primed (for those wishing to custom paint or stain their door)
Coachman®		15 Door Designs, 10 Window or Solid Top Section Designs	Carriage House	18", 21", 24"	4 Layers: Steel + 2" Intellcore® Polyurethane Insulation + Steel + Composite ¹ Steel + 2" Bonded Polystyrene Insulation + Steel + Composite ¹ Steel + 1-3/8" Bonded Polystyrene Insulation + Steel + Composite	Base: Standard White, Almond, Desert Tan, Sandtone Overlay: Standard White, Almond, Desert Tan, Sandtone
Grand Harbor®		8 Door Designs, 16 Window or Solid Top Section Designs	Carriage House	18", 24"	3 or 2 Layers: Composite + Steel + Insulation, Composite + Steel	Base: Standard White, Almond, Desert Tan, Sandtone Overlay: Standard White
Gallery® Steel	Three-Layer	2 Door Designs, 25 Window or Solid Top Section Designs	Carriage House	18", 21", 24"	3 Layers: Steel + 2" Intellcore® Polyurethane Insulation + Steel ¹ Steel + 1-3/8" Intellcore® Polyurethane Insulation + Steel ¹ Steel + 2" Bonded Polystyrene Insulation + Steel ¹ Steel + 1-3/8" Bonded Polystyrene Insulation + Steel	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Ultra-Grain® Oak: Medium, Dark, Walnut and Slate Finishes
Gallery® Steel	Two-Layer and One-Layer	2 Door Designs, 25 Window or Solid Top Section Designs	Carriage House	18", 21", 24"	2 or 1 Layers: Steel + 1-5/16" Polystyrene Insulation; Steel	Standard White, Almond, Desert Tan, Sandtone, Chocolate*
Bridgeport™ Steel	Three-Layer	2 Door Designs, 25 Window or Solid Top Section Designs	Shaker (Narrow and Extended Recessed)	18", 21", 24"	3 Layers: Steel + 2" Intellcore® Polyurethane Insulation + Steel ¹ Steel + 1-3/8" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Ultra-Grain® Oak: Medium, Dark, Walnut and Slate Finishes
Garage Door	Type	Model/Design	Door/Panel Style	Sect. Hts.	Construction/Material	Colors
Modern Steel™	Premium	9202, 9201, 9208 No Panel	Modern Flush	18", 21", 24"	3 Layers: Steel + 2" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green†, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes**
Modern Steel™	Premium	9205, 9209 No Panel	Modern Grooved	18", 21", 24"	3 Layers: Steel + 2" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes
Modern Steel™	Premium	9132, 9138 No Panel 9131	Modern Flush	18", 21", 24" 18", 21"	3 Layers: Steel + 1-3/8" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green†, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes**
Modern Steel™	Premium	9139 No Panel	Modern Grooved	18", 21", 24"	3 Layers: Steel + 1-3/8" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes
Modern Steel™	Premium	4302, 4308 No Panel 4301	Modern Flush	18", 21", 24" 18", 21"	3 Layers: Steel + 2" Bonded Polystyrene Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green†, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes**
Modern Steel™	Premium	4305, 4309 No Panel	Modern Grooved	18", 21", 24"	3 Layers: Steel + 2" Bonded Polystyrene Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes
Modern Steel™	Premium	4132 No Panel	Modern Flush	18", 21", 24"	3 Layers: Steel + 1-3/8" Bonded Polystyrene Insulation + Steel	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes
Modern Steel™	Premium	4051 No Panel	Modern Flush	18", 21"	3 Layers: Steel + 1-3/8" Bonded Polystyrene Insulation + Steel	Standard White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Hunter Green, Gray
Modern Steel™	Premium	4138 No Panel	Modern Flush	18", 21", 24"	3 Layers: Steel + 1-3/8" Bonded Polystyrene Insulation + Steel	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Gray, Ultra-Grain® Cypress: Medium, Cherry, Walnut and Slate Finishes
Modern Steel™	Value	4F, 4F4 No Panel	Modern Flush	18", 21"	1 Layer: Steel	Standard White, Almond, Desert Tan, Sandtone, Chocolate
Classic™ Steel	Premium	9200 Raised Panel	Elegant Short	18", 21"	3 Layers: Steel + 2" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green, Gray, Ultra-Grain® Classic: Medium, Cherry and Walnut Finishes
Classic™ Steel	Premium	9203 Raised Panel	Elegant Long	18", 21"	3 Layers: Steel + 2" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green, Gray, Ultra-Grain® Classic: Medium, Cherry and Walnut Finishes
Classic™ Steel	Premium	9130 Raised Panel	Elegant Short	18", 21"	3 Layers: Steel + 1-3/8" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green, Gray, Ultra-Grain® Classic: Medium, Cherry and Walnut Finishes
Classic™ Steel	Premium	9133 Raised Panel	Elegant Long	18", 21"	3 Layers: Steel + 1-3/8" Intellcore® Polyurethane Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green, Gray, Ultra-Grain® Classic: Medium, Cherry and Walnut Finishes
Classic™ Steel	Premium	4300 Raised Panel	Elegant Short	18", 21"	3 Layers: Steel + 2" Bonded Polystyrene Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green, Gray, Ultra-Grain® Classic: Medium, Cherry and Walnut Finishes
Classic™ Steel	Premium	4310 Raised Panel	Elegant Long	18", 21"	3 Layers: Steel + 2" Bonded Polystyrene Insulation + Steel ¹	Standard White, Glacier White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Mocha Brown, Charcoal, Black, Hunter Green, Gray, Ultra-Grain® Classic: Medium, Cherry and Walnut Finishes
Classic™ Steel	Premium	4050 Raised Panel	Elegant Short	18", 21"	3 Layers: Steel + 1-3/8" Bonded Polystyrene Insulation + Steel	Standard White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Hunter Green, Gray
Classic™ Steel	Premium	4053 Raised Panel	Elegant Long	18", 21"	3 Layers: Steel + 1-3/8" Bonded Polystyrene Insulation + Steel	Standard White, Almond, Desert Tan, Sandtone, Bronze, Chocolate, Hunter Green, Gray
Classic™ Steel	Value Plus	1500 and 15SP Raised Panel	Traditional Short	18", 21"	2 Layers: Steel + 1-5/16" Polystyrene Insulation	Standard White, Almond, Desert Tan, Sandtone, Chocolate
Classic™ Steel	Value Plus	76V and 76VSP Raised Panel	Traditional Long	18", 21"	2 Layers: Steel + 1-5/16" Polystyrene Insulation	Standard White, Almond, Desert Tan, Sandtone, Chocolate
Classic™ Steel	Value ²	73 and 94 Raised Panel	Traditional Short	18", 21"	1 Layer: Steel	Standard White, Almond, Desert Tan, Sandtone, Chocolate
Classic™ Steel	Value ²	76 Raised Panel	Traditional Long	18", 21"	1 Layer: Steel	Standard White, Almond, Desert Tan, Sandtone, Chocolate
Garage Door	Type	Model/Design	Door/Panel Style	Sect. Hts.	Construction/Material	Finishing Options
Reserve® Wood	Custom	Custom	Carriage House	Varies	5 or 4 Layers: Specified Wood; Insulated	Stained, Finish Painted White, Primed, Unfinished
Reserve® Wood	Limited Edition	8 Door Designs, 13 Window or Solid Top Section Designs	Carriage House	Varies	5 or 4 Layers: Meranti, Cedar, Redwood, Fir, Exdura®, Luan; Insulated	Stained, Finish Painted White, Primed, Unfinished
Reserve® Wood	Modern	3 Door Designs	Contemporary	Varies	4 Layers: Light Cedar, Dark Cedar, Mixed Cedar, Redwood, Fir, Meranti	Stained, Finish Painted White, Primed, Unfinished
Reserve® Wood	Semi-Custom	6 Door Designs, 10 Window or Solid Top Section Designs	Carriage House	22.75", 28"	2 Layers: Hemlock, Cedar, Redwood, Exdura®	Stained, Finish Painted White, Primed, Unfinished

*Not available on 24 gauge, long panel models.

**Not available on Models 9201, 9131 and 4301.

†Not available on Models 9202, 9208, 9132, 9138, 4302, 4308.

Glacier White and Mocha Brown are not available on impact windows. Additional charges for optional glass apply.

Clopay's patents mentioned throughout are 9,022,091 for impact windows, D719,280 and D755,409 for tapered strut.

¹Not all models available in all regions. See your Clopay Dealer for model availability in your region.

²Models come standard with 10-ball nylon rollers and heavy-duty 14 gauge steel hinges. These models also comply with 2015 IECC air infiltration requirement of 0.40 cfm/ft² or less (IECC, Section C402.5.2).

Effective April 2021

(Subject to change without notice)



Visit clopaydoor.com or call 1-800-2CLOPAY (225-6729) for more information on Clopay, America's Favorite Garage Doors.

Follow us on



MADE IN USA



imagine



DESIGN YOUR DOOR
OPEN CAMERA
AND POINT!

©2021 Clopay Corporation. All rights reserved.

RSDR-WC8R-12_REV0421